

ISPS2013-2951

H_∞ CONTROL DESIGN FOR SYSTEMS WITH PERIODIC IRREGULAR SAMPLING USING OPTIMAL H_2 REFERENCE CONTROLLERS

Behrooz Shahsavari

Department of Mechanical Engineering
University of California
Berkeley, California 94720
Email: behrooz@berkeley.edu

Richard Conway

Department of Mechanical Engineering
University of California
Berkeley, California 94720
Email: rconway345@gmail.com

Ehsan Keikha

Department of Electrical and
Computer Engineering
National University of Singapore
Singapore, 117576
Email: keikha@berkeley.edu

Fu Zhang

Department of Mechanical Engineering
University of California
Berkeley, California 94720
Email: shallen@berkeley.edu

Roberto Horowitz

Department of Mechanical Engineering
University of California
Berkeley, California 94720
Email: horowitz@berkeley.edu

ABSTRACT

This paper presents a novel robust H_∞ control design for linear systems with periodic irregular sampling and regular actuation rates. A three-step design algorithm is developed to design a controller that achieves high robustness in terms of disk margin, and high performance in terms of root mean square (RMS) of 3σ -value of performance signal. The proposed method is exploited to design a track-following controller for a hard disk drive (HDD) with 30% sampling time irregularity. The simulation study presented in this paper shows the effectiveness of the proposed control design for high-order systems with large periods.

1 INTRODUCTION

Optimal H_∞ control design is one of the most popular methodologies for synthesizing control systems that achieve robust performance or stabilization. In [1] an explicit solution for optimal H_∞ control synthesis via discrete Riccati equations for LPTV systems is proposed. The authors provided an H_∞ control synthesis based on loop-shaping methods. The performance

and robustness of the controller designed by this method strongly depends on the selection of appropriate loop-shaping weighting functions, which is not generally a trivial process and needs several manual iterations. In this paper, we use a novel discretization method proposed in [2] to find an LPTV model for a system with periodic irregular sampling. The control design algorithm in this paper consists of two main steps. In the first step, a linear quadratic Gaussian (LQG) control problem with a constraint on variance of the control signal is solved using the results of [2]. Once the LQG controller is designed, it will be exploited in the second step of the control design algorithm, in which an optimal LPTV H_∞ controller will be designed.

Since the system is LPTV, it is not possible to use classical gain and disk margins as the measures of robustness. Instead, we characterize the robustness of this type of systems by using an idea known as “disk margin”, which can be calculated by computing the H_∞ norm of a modified closed loop system. Therefore, the controller design can be formulated as an optimal H_∞ problem that aims to achieve two objectives. The first objective is the minimization of the H_∞ norm associated with the disk margin of the system, and the second objective is to minimize the H_∞ norm




FIGURE 1: ARCHITECTURE USED FOR CONTROL DESIGN

of the error between the outputs of the constrained LQG and the H_∞ controller that is being designed. This multi-objective optimization problem is replaced by a single-objective H_∞ optimization problem, which is solved by periodic Riccati equations.

CONTROL DESIGN

The control objective throughout this paper is to maximize the robustness of the closed-loop system while maintaining good performance. We use the method proposed in [3] to calculate the disk margin of the system as a measure of robustness for LPTV systems. The architecture we use for control design is shown in Fig. 1. The blocks G , K_2 and K_∞ are respectively the plant model, optimal LQG controller and optimal H_∞ controller that will be calculated through the steps of design algorithm. Block M is a constant matrix and defined by $M := \begin{bmatrix} 1, \sqrt{2} \\ \sqrt{2}, 1 \end{bmatrix}^T$.

The H_∞ norm from d_3 to z_2 gives the disk margin of the closed-loop system. It should be noticed that the output of K_2 does not enter the closed loop system. Hence, for a fixed K_∞ and K_2 the performance and robustness of the system are only functions of K_∞ . Although the actual plant is single-input single-output (SISO), the particular discretization method used here introduces two signals, y_1 and y_2 , to model the output dynamics (more details in subsection 1.1). Signal e in Fig. 1 corresponds to the error between the output of the optimal H_∞ controller and H_2 controller. Hence the H_∞ norm of the closed loop system from all the inputs to this output will be small when the dynamics of K_∞ controller is close to the dynamics of K_2 . Finally, signals d_1 and d_2 are two fictitious disturbances added to the outputs of the plant to satisfy the regularity conditions required for the solution of H_∞ control design [1].

1.1 Constructing the plant model

We use the method proposed in [3] to find an LPTV model for a system with periodic irregular sampling. For such a system control update can be either clock-driven (i.e. regular in time) or event-driven (e.g. updating control as soon as obtaining a mea-




FIGURE 2: IRREGULAR SAMPLING (CIRCLES) AND IRREGULAR ACTUATION (CROSSES) RATES




FIGURE 3: IRREGULAR SAMPLING (CIRCLES) AND REGULAR ACTUATION (CROSSES) RATES




FIGURE 4: ARCHITECTURE USED FOR DESIGNING H_2 REFERENCE CONTROLLER

surement). As illustrated in [2] the former scheme can result in better closed-loop performance for the type of systems studied in this work. Therefore, we use a clock-driven control update scheme throughout this paper. In this control scheme, there is no fixed relationship between the times at which measurements are obtained and the times at which the control is updated. Hence, the number of samples in the time interval S_k (c.f. 3) is not necessarily constant over k . For simplicity, we will consider a situation in which 0, 1, or 2 measurements may be made in any time interval S_k . Regardless of how many measurements are placed in a time interval S_k , we assume that the system has always 2 outputs, which are denoted as y_1 and y_2 in Fig. 1 (e.g. $y := [y_1, y_2]^T$ where y is the output vector). When there is just one available output, say y_1 , the other element of the output signal, y_2 , will be zero. Similarly when there is no available outputs, both of the elements of the output vector will be zero. It is noteworthy that this assumption makes the system structure time invariant.

1.2 Designing optimal LQG controller (K_2)

We design an optimal LQG controller subject to a constraint on variance of the control signal for the plant model described in subsection 1.1. This optimal control problem is presented in [2]

and the control design architecture is shown in Fig. 4. The block \bar{G} in that figure represents the dynamics of the plant and disturbances. Indeed, \bar{G} is an LPTV state space system from the disturbances and control signal to the performance (p), control signal (u) and measurement vector (m). The disturbance dynamics is modeled and implanted in \bar{G} such that the signal d is white noise with identity covariance. This controller will achieve the minimum RMS $3\text{-}\sigma$ value of p when the mean variance of u is constrained to be less than or equal to a required value. This value will be chosen by the designer and corresponds to the maximum reasonable power to the actuator.

Since the robustness of the closed loop system is not considered in the design of K_2 , we cannot guarantee a lower bound on the robustness of the closed loop system. To solve this problem and increase the robustness of the system we consider the next step.

1.3 Designing optimal H_∞ controller (K_∞)

Once the K_2 controller is designed, we choose three static values for the weighting parameters, W_1 , W_2 and W_e , and form the interconnection shown in Fig. 1 to calculate K_∞ . For large values of W_e the effect of system dynamics from the inputs to z_2 will be negligible. In the absence of z_2 , the H_∞ norm of the closed loop system will be minimum and equal to zero when $K_\infty = K_2$. In this case the system will have the highest achievable performance. In contrast, when W_e is close to zero, the minimization of the H_∞ norm of the system will result in large disk margin, because the H_∞ norm from d_3 to z_2 will be small which is conversely related to the robustness of the closed-loop system. Accordingly, increasing and decreasing the value of W_e will respectively result in increasing the performance and robustness of the system.

The other two scaling parameters, W_1 and W_2 , are just considered to make the feed-through term from uncontrollable inputs to measurements in the dynamics of the open loop system non-zero; this is one of the regularity conditions required for the solution of the optimal H_∞ problem [4]. Once all the design parameters are chosen, K_∞ can be calculated by the method proposed in [1].

SIMULATION STUDY

To show the effectiveness of the proposed method, a robust H_∞ controller is designed for track-following in a hard disk drive. Sampling intervals for hard disk drive servo systems are not always equidistant over a revolution of the disk. Since HDDs are naturally periodic, with period equal to the time for one rotation of the disk, the servo system from the control input to the position error signal (PES) can be represented by an LPTV system whose period is the number of servo sectors, N . The order of the plant model we use is 18 and the period (N) is 400. We assume that the sampling time profile is sinusoidal with period equal to one




FIGURE 5: PERFORMANCE VS ROBUSTNESS OF HDD

revolution of the disk and the variation from minimum to maximum sampling interval is 60% of the nominal sampling time. The performance (in terms of RMS of 3σ value of PES) versus the robustness (in terms of disk gain margin) is shown in Fig. 5. The point denoted as LQG represents the performance and robustness characteristics of the H_2 reference controller (designed in step 2), which has the best performance but inadequate robustness. Each plot corresponds to a fixed value of W_e and consists of seven points corresponding to different values of W , where $W = W_1 = W_2$. The values of W are shown next to each data point. As expected, for fixed values of W , increasing W_e increases the robustness; in contrast, decreasing this value boosts the performance of the closed loop system. As a result, when 5 dB of gain disk margin and 5% track of PES 3σ are required (shaded region in Fig. 5) the appropriate controller can be designed by choosing $W_e = 0.25$ and $W = 8$.

REFERENCES

- [1] Nie, J., Conway, R., and Horowitz, R., 2010. "Optimal h control for linear periodically time-varying systems in hard disk drives". In Proc. of the 2010 Dynamic Systems and Control Conference.
- [2] Shahsavari, B., Conway, R., Keikha, E., and Horowitz, R., 2013. "Limits of performance in systems with periodic irregular sampling and actuation rates". In Proc. of 6th IFAC Symposium on Mechatronic Systems, Hangzhou, China.
- [3] Shahsavari, B., Conway, R., Keikha, E., Zhang, F., and Horowitz, R., 2013. "Robust track-following controller design for hard disk drives with irregular sampling". to appear in *IEEE Transactions on Magnetics*.
- [4] Peters, M. A., and Iglesias, P. A., 1997. *Minimum entropy control for time-varying systems*. Birkhauser.